

# **Highly Selective H<sub>2</sub> Separation Zeolite Membranes for Coal Gasification Membrane Reactor Applications**

## **ABSTRACT**

**Professors Richard D. Noble and John L. Falconer  
University of Colorado at Boulder  
Department of Chemical Engineering  
424 UCB Boulder CO 80309-0424**

The objective of the research proposal is to prepare zeolite membranes that will be capable of highly selective H<sub>2</sub> separation from other light gases (CO, CO<sub>2</sub>, H<sub>2</sub>O) for use in catalytic membrane reactor applications related to coal conversion and gasification. These zeolite membranes have the potential to operate over a wide temperature and pressure range and in chemically challenging environments where existing technologies are inefficient or unable to operate.

The approach will address the two fundamental properties associated with membrane separations: flux and selectivity. To date, membranes have not been developed that are mechanically and chemically stable and can provide a highly selective separation of H<sub>2</sub> from other light gases at elevated temperatures and in chemically challenging conditions associated with coal gasification. At elevated temperatures, the gas flux will be inversely proportional to the membrane thickness. We propose to synthesize thinner, defect-free zeolite membranes through the use of a covalent linking method to attach seed crystals to the support prior to the actual synthesis. Initial results with B-ZSM-5 zeolite membranes have shown that we can get up to a five-fold increase in flux with this approach. To obtain high selectivity for this separation at elevated temperatures, the membrane must be capable of molecular sieving. The membrane will have to discriminate between molecules that are approximately 0.3-0.4 nm in size and 0.1 nm or less in size difference. To accomplish this sieving, we propose to synthesize small pore zeolite membranes that have pores in this size range [Type A (0.42 nm) and chabazite (0.38 nm)]. We will then post-treat them to systematically reduce the pore size and the non-zeolite pores (grain boundaries) using three different methods: CVD (chemical layer deposition), and ALD (atomic layer deposition) and photopolymerization. These post-treatment procedures should give us the flexibility to tune the pore size and resulting selectivity with high precision. This approach will also allow us to use these membranes for other types of membrane reactor applications such as dehydrogenation reactions where the molecular size difference between H<sub>2</sub> and the other components is larger.